

SERIES 5010 Window Washing System IDEAL FOR WASHING BRIDGE WINDOWS

- Cost effective, compact, off-the-shelf window washing module
- High water pressure through adjustable nozzles giving total window spray coverage
- Heated water giving rapid dispersal of salt deposits
- Detergent injection to remove grease and oil residue
- Air purge facility to clear water line
- Optional anti-freeze mix for arctic operations
- High quality and proven components to give reliable and long-life service
- Flexible network controls



OF VESSEL SYSTEMS FOR ALL SIZES





Phone: (225) 644-7063 Fax: (225) 644-7046 Web: www.inmarsystems.com







Phone: (225) 644-7063 Fax: (225) 644-7046

Web: www.inmarsystems.com

SPECIFICATIONS

Supply capacity Up to 10 nozzles simultaneously, plus 10 with additional valves.

Nozzles Spray nozzles give a uniform flat spray delivering up to 2 litres/min at 5 bar.

Wash pump Maximum of 6 bar operating up to 80°C. The pump delivers up to

10 litres/min at 5 bar.

Storage tanks 60 litre water tank (fitted with low level indicator).

Motors 115v or 230v AC 1-phase 50/60Hz, Class F insulation and IP44 rating.

24, 115v or 230v AC 1-phase - pipe diameter to be specified. Solenoid valves

Heater 115v or 230v AC 1-phase 3Kw - with adjustable thermostat

Weight and Dimensions 130W x 100H x 55D cm (approx excl. mountings) from 60kg (approx, dry).

Controls Cable incorporated into Wynn wiper control systems, or via a dedicated

wash system control panel.

HOW TO ORDER

Washing systems are custom made to meet your requirements. Please advise the following:


1 Quantity of spray nozzles required?


2 Voltage / Power supply?


3 Heated water mix: Yes / No

4 Detergent mix: Yes / No











Series 5010 Window Washing System

> IDEAL FOR WASHING **BRIDGE WINDOWS**

