

Phone: (225) 644-7063 Fax: (225) 644-7046

Web: www.inmarsystems.com

TYPES C&D

Heavy Duty Straightline Wipers

IDEAL FOR LARGE OCEAN-GOING VESSELS OR VESSELS REQUIRING MAXIMUM COVERAGE

- Type D MkV Externally mounted motor. Motor housing fully sealed to IP67
- Type C Internally mounted motor
- Arms with blades up to 2000mm available
- A large wiped window coverage can be achieved
- Reliable operation in extreme temperatures
- 2 or 3 speed operation with self parking facility
- Available in 24, 115 and 230 volt, single phase or three phase AC
- Operated by a multi-speed / function control facility
- Induction motor
 (brushes) are
 used for AC supplies







Type D MkV





















The heavy duty Type D (externally mounted motor) and Type C (internally mounted motor) straightline wipers offer the most advanced design of linear action window wiping systems for marine and other specialist applications.

A large wiped window coverage can be achieved, providing maximum view from the ships bridge whatever the weather, in temperatures from as low as -40°C to extreme tropical conditions. High powered AC induction motors provide an efficient, reliable and quiet operation. Incorporating the highest quality 316 Stainless Steel and other noncorrosive materials throughout, the Type D has the motor outboard so that it is only necessary to bring the electrical cables through the bulkhead. the motor housing is fully sealed to IP67 standards.

Standard controllers are available in 1-6 ways, with modular systems being supplied where there are more wipers or have a special requirement. Control features can include 2 or 3 speed operation, self parking, intermittent wipe, heater switch, master group control and wash/air purge functions.

SPECIFICATIONS

Single

Stroke Minimum - 305mm Maximum - 2260mm Maximum - 2000mm Blade Maximum - 1500mm Arm

Twin

De-icing heater

Mounting

Stroke Minimum - 585mm, Maximum - 3500mm

(over 3500mm can be supplied upon

request)

Maximum - 1000mm Blade Maximum - 800mm Arm

Wipe Speed: fast/slow 1.4m per second / 0.7m per second AC Motor Induction type: 100, 115, 230v DC Motor Permanent magnet; 24v

3-PH Motor Fast speed / slow speed / intermittent 1-PH and DC

Normal speed / intermittent

8000 motor 3 speed 0.7/1.1/1.4n/sec


200 watts per metre


Reed switch Park Sensor

Spray Nozzles 1 up to 990mm stroke, 2 if > 1015mm stroke, 6mm overall diameter tubing


Above, below or vertical on the window

Type Approvals DNV. ABS





*Measurements are for illustrative purposes only





Phone: (225) 644-7063 Fax: (225) 644-7046 Web: www.inmarsystems.com

Types C&D Straightline Wipers

IDEAL FOR LARGE OCEAN-GOING VESSELS

Can be used in combination with the following Controllers:

Control Systems

- 1000 (1 speed only)
- 2000 (2 speed)
- 6000 (2 speed)
- 8000 (3 speed)

